

Durapipe Ref. No: DO921
Issue Date - February 2007



**MATERIAL SAFETY DATA SHEET
ACCORDING TO 91/155 EC**

DURAPIPE AIR-LINE XTRA SOLVENT CEMENT

1. IDENTIFICATION OF SUBSTANCE

Product details

Trade name: Durapipe Air-line XTRA Solvent Cement
Application of the substance / the preparation: Adhesive
Manufacturer/Supplier: Durapipe UK
Walsall Road, Norton Canes, Staffordshire WS11 9NS, England

Email: enquiries@durapipe.co.uk
Website: www.durapipe.co.uk

Tel: 00 44 (0) 1543 279 909
Fax: 00 44 (0) 1543 279 450

Further information available from: Technical Support Department, Tel 0044 (0)1543 272445

Information in case of emergency: Technical Support Department, Tel 0044 (0)1543 272445

2. CHEMICAL COMPOSITION

Description: Adhesive

Dangerous components:

	CAS No.	Classification	Content	EC No.
Methylethylketone	78-93-3	Xi F R-11, 36, 66, 67	50 - 100 %	201-159-0
Acetone	67-64-1	Xi F R-11, 36, 66, 67	2,5 - 10 %	200-662-2
Tetrahydrofuran	109-99-9	Xi F R-11, 19, 36, 37	2,5 - 10 %	203-726-8

3. HAZARDS IDENTIFICATION

Hazard description: Xi Irritant
F Highly flammable

Information concerning to particular hazards to man and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Has a narcotizing effect.

R 11 Highly flammable.

R 36 Irritating to eyes.

R 66 Repeated exposure may cause skin dryness or cracking.

R 67 Vapours may cause drowsiness and dizziness.

Classification system: The classification is according to the latest editions of the EU-lists, and extended by company and literature data.



4. FIRST AID MEASURES

After inhalation:	Supply fresh air; consult doctor in case of complaints.
After skin contact:	Generally the product does not irritate the skin.
After eye contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing:	Do not induce vomiting; call for medical help immediately.

5. FIRE FIGHTING MEASURES


Suitable extinguishing agents:	Water haze Alcohol resistant foam Fire-extinguishing powder Carbon dioxide
For safety reasons unsuitable extinguishing agents:	Water with full jet
Protective equipment:	Mount respiratory protective device.
Additional information:	Cool endangered receptacles with water spray. Collect contaminated fire fighting water separately. It must not enter the sewage system.

6. ACCIDENTAL RELEASE MEASURES

Person-related safety precautions:	Wear protective equipment. Keep unprotected persons away.
Measures for environmental protection:	Prevent seepage into sewage system, workpits and cellars. Do not allow to enter sewers/ surface or ground water.
Measures for cleaning/collecting:	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

7. HANDLING AND STORAGE

Handling:	
Information for safe handling:	Ensure good ventilation/exhaustion at the workplace. Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Information about fire - and explosion protection:	Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
Storage:	
Requirements to be met by storerooms and receptacles:	Store in a cool location.
Information about storage in one common storage facility:	Not required.
Further information about storage conditions:	Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.





8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Additional information about design of technical facilities:

No further data; see item 7.

Ingredients with limit values that require monitoring at the workplace:

	78-93-3 methyl ethyl ketone	
WEL: Short-term value:	899 mg/m ³ ,	300 ppm
Long-term value:	600 mg/m ³ ,	200 ppm
	67-64-1 acetone	
WEL: Short-term value:	3620 mg/m ³ ,	1500 ppm
Long-term value:	1210 mg/m ³ ,	500 ppm
	109-99-9 tetrahydrofuran	
WEL: Short-term value:	300 mg/m ³ ,	100 ppm
Long-term value:	150 mg/m ³ ,	50 ppm

Additional information: The lists valid during the making were used as basis.

Personal protective equipment: General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection: Not required.

Protection of hands: Protective gloves
Solvent resistant gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
PVC or PE gloves


Eye protection: Tightly sealed goggles

Body protection: Solvent resistant protective clothing

9. PHYSICAL AND CHEMICAL PROPERTIES

General Information

Form: Fluid
Colour: According to product specification



Odour:	Characteristic
Value/Range Unit Method	
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55 ° C
Flash point:	< 0 ° C
Ignition temperature:	230 ° C
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.8 Vol %
Upper:	11.5 Vol %
Vapour pressure:	at 20°C 105 hPa
Density:	at 20°C 0.86 g/cm ³
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Viscosity:	
Dynamic:	at 20°C 1500 mPas
Solids content:	24.5 %

10. STABILITY AND REACTIVITY

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Dangerous reactions:

No dangerous reactions known.

Dangerous decomposition products:

Danger of forming toxic pyrolysis products.

11. TOXICOLOGICAL INFORMATION

Acute toxicity:

Primary irritant effect:

on the skin:

No irritant effect.

on the eye:

Irritating effect.

Sensitization:

No sensitizing effects known.

Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

12. ECOLOGICAL INFORMATION

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13. DISPOSAL CONSIDERATIONS

Product:

Recommendation:

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations. Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14. TRANSPORT INFORMATION

Land transport ADR/RID (cross-border)
 ADR/RID class: 3 (F1) Flammable liquids.
 Danger code (Kemler): 33
 UN-Number: 1133
 Packaging group: II
 Hazard label 3
 Description of goods: 1133 ADHESIVES, special provision 640H
 Maritime transport IMDG:
 IMDG Class: 3
 UN Number: 1133
 Label 3
 Packaging group: II
 EMS Number: F-E,S-D
 Marine pollutant: No
 Proper shipping name: ADHESIVES
 Air transport ICAO-TI and IATA-DGR:
 ICAO/IATA Class: 3
 UN/ID Number: 1133
 Label 3
 Packaging group: II
 Proper shipping name: ADHESIVES

Remarks: Not submit to ADR/VLG in small packing in original outside packing with UN number placed inside diamond shaped label (Limited quantity)

15. REGULATORY INFORMATION

Labelling according to EU guidelines: The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product:
 Xi Irritant
 F Highly flammable

Risk phrases:
 11 Highly flammable.
 36 Irritating to eyes.
 66 Repeated exposure may cause skin dryness or cracking.
 67 Vapours may cause drowsiness and dizziness.

Safety phrases:
 9 Keep container in a well-ventilated place.
 16 Keep away from sources of ignition — No smoking.
 24/25 Avoid contact with skin and eyes.
 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 46 If swallowed, seek medical advice immediately and show this container or label.
 51 Use only in well-ventilated areas.

National regulations:

Technical instructions (air):

Class Share in %
 II 2,5-10
 III 50-100

Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.



16. OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant R-phrases	11	Highly flammable.
	19	May form explosive peroxides.
	36	Irritating to eyes.
	36/37	Irritating to eyes and respiratory system.
	66	Repeated exposure may cause skin dryness or cracking.
	67	Vapours may cause drowsiness and dizziness.

Department issuing MSDS: Marketing Department

Contact: Roy Shepherd, Technical Support Manager, Tel 0044 (0)1543 272445

* Data compared to the previous version altered.

